

Substrate		DIN 60001,ASTM D7641	100% Polyester
Weave			Warp-knitted 2 bar
Yarn		DIN EN 2060,ASTM D1907	55D*75D
Weight approx.		ISO536	260 gsm, 7.7oz/yd
Shrinkage		200°C/45s	5.05m:≤4%, 3.2m:≤3%
Opacity		ISO2471	>99%
Elasticity		Warp:(3±2)% Weft:(2±1)%	Length*Width=200*50mm,Speed=100mm/min,Tension=20N
Fire retardancy		DIN 4102-1 B1,NFPA 701 ,EN13501-1	
Recommend Fixation Temperature			190-200°C,45s
Yellowing Temperature		SUPRKC REX-C400,30s	≥ 210°C
Application			indoor
Width			260, 320, 505cm / 102, 126, 199 inches
Roll length			50, 100 m / 55, 109yd
Type of ink		DS DIRECT DS TRANSFER UV	
Environmental elements		PVC No PVC VOC Low-VOCs Emission Heavy Metal No Heavy Metal DOP DOP Free	

Advantages

- 100% Recyclable
- Soft touch and feel
- Blockout
- Crease Resistant
- REACH compliant

Applications

- Exhibition graphics
- Blackout
- Display system
- Tension Frames
- Wall Hangings