

370

370 gr



decal art canvas 370

100% cotton fabric with a matte surface, excellent print quality and high stability. It also has brilliant color reproduction and dries quickly.

SUBSTRATE

- 100% Cotton Fabric

Finish	White Matte		
	<i>Value</i>	<i>Tolerance</i>	<i>Standard</i>
Weight (g/m2)	370	± 15g	Digidelta Test Method
Thickness (mic)	420	± 15%	Digidelta Test Method
Service temperature °C	0 a 50		

decal art canvas 370

DURABILITY

- DURABILITY: < 5 years
 - Shelf Life: 12 months from the date of manufacture, applicable only to material that has not been processed, and stored according to the following conditions:
 - This material must be stored at a temperature of 20° C ± 5 ° C and 50% ± 5% relative humidity, without major climate deviations.
 - The storage area must be dry and clean.
 - Keep the material in the original package when not in use, in order to protect it from dust and contamination.
 - Do not expose to direct sunlight or heat sources.
 - The product must be stored vertically, so that its quality is not compromised.
-

PRINTING METHODS

- Specially developed for eco-solvent and UV printing.
 - Excessive ink on the product will result in changes to its characteristics, improper drying, delamination, and/or poor product performance.
 - To achieve the best possible print quality, ensure you are using the correct print profiles.
 - Inadequate drying can result in curling and wrinkling, affecting the material's performance.
 - A minimum drying time of 48 hours is recommended before any further processing. Drying should be done with the product unwound.
-

APPLICATION

- Surface for application: flat.
 - Not recommended for floor graphics (areas with vehicle traffic); flexible or low-energy substrates; non-flat surfaces; painted or unpainted drywall; plaster walls; wallpaper; dirty or rough surfaces; surfaces with degraded paint.
 - Printed materials must be adequately dried before processing or application.
 - Do not expose to combustible vapors or spills.
 - Non-vertical application significantly reduces durability, as do climatic conditions and solar exposure angles.
 - Before using the material, we recommend it remain at workplace temperature for at least 24 hours.
 - Other factors not described may influence performance during use.
-

IMPORTANT REMARKS

- The data provided in this information is based on our knowledge and practical experience. It is intended as a source of information and does not constitute a guarantee. Subject to change without notice.
- The user must determine the compatibility of the material with the intended specific application before use.
- We recommend using the same batch of product for a job.
- Decal is not responsible for misuse or improper storage and cannot be held liable for losses or damages to third parties.

Revision date of the technical data sheet: 24/10/24
Approved by: SC

Please, check our website www.decal-adhesive.com for additional information or request any clarification needed from our technicians.