



frontlit
coated



450 gr



decal banner FC 450

White banner, with a matt finish, 1000x1000 Denier base yarn and 18x18 inch weft density, with high flexibility, resistance to tearing and temperature differences.

The special surface coating optimises ink adhesion and colour reproduction for long-lasting prints.

FACE MATERIAL

- Coated Banner

Finish	White Matte		
	<i>Value</i>	<i>Tolerance</i>	<i>Standard</i>
Weight (g/m2)	450	± 15g	DIN 53352
Amount of thread (D)	1000*1000		Digdelta Test Method
Mesh (sq.in)	18*18 (sq.in)		Digdelta Test Method
Service temperature °C	-15 a 70		

decal banner FC 450

DURABILITY

- DURABILITY: < 12 months
 - Shelf Life: 12 months from the date of manufacture, applicable only to material that has not been processed, and stored according to the following conditions:
 - This material must be stored at a temperature of $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and $50\% \pm 5\%$ relative humidity, without major climate deviations.
 - The storage area must be dry and clean.
 - Keep the material in the original package when not in use, in order to protect it from dust and contamination.
 - Do not expose to direct sunlight or heat sources.
 - The product must be stored vertically, so that its quality is not compromised.
-

PRINTING METHODS

- Specially developed for solvent, eco-solvent, and UV printing.
 - Excessive ink on the product will result in changes to its characteristics, improper drying, delamination, and/or poor product performance.
 - To achieve the best possible print quality, ensure you are using the correct print profiles.
 - Inadequate drying can result in curling and wrinkling, affecting the material's performance.
 - A minimum drying time of 48 hours is recommended before any further processing. Drying should be done with the product unwound.
-

APPLICATION

- Printed materials must be adequately dried before processing or application.
 - Do not expose to combustible vapors or spills.
 - Non-vertical application significantly reduces durability, as do climatic conditions and solar exposure angles.
 - Other factors not described may influence performance during use.
-

IMPORTANT REMARKS

- The data provided in this information is based on our knowledge and practical experience. It is intended as a source of information and does not constitute a guarantee. Subject to change without notice.
- The user must determine the compatibility of the material with the intended specific application before use.
- We recommend using the same batch of product for a job.
- Decal is not responsible for misuse or improper storage and cannot be held liable for losses or damages to third parties.

Revision date of the technical data sheet: 23/10/24
Approved by: SC

Please, check our website www.decal-adhesive.com for additional information or request any clarification needed from our technicians.