



frontlit
laminated



high tear
resistance



440 gr



decal banner FL HTR 440

White PVC-laminated polyester canvas with 440g/m², 1000x1000 Denier base yarn and 9x9 inch weft density, which gives it excellent tear resistance. The special surface coating optimises ink adhesion and colour reproduction for long-lasting prints.

FACE MATERIAL

- Laminated Banner

Finish	White Glossy	White Matte	Tolerance	Standard
	Value	Value		
Weight (g/m ²)	440	440	± 15g	DIN 53352
Amount of thread (D)	1000*1000	1000*1000		Digidelta Test Method
Mesh (sq.in)	9*9	9*9		Digidelta Test Method
Service temperature °C	-10 a 60	-10 a 60		

decal banner FL HTR 440

DURABILITY

- DURABILITY: < 6 months
 - Shelf Life: 12 months from the date of manufacture, applicable only to material that has not been processed, and stored according to the following conditions:
 - This material must be stored at a temperature of $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and $50\% \pm 5\%$ relative humidity, without major climate deviations.
 - The storage area must be dry and clean.
 - Keep the material in the original package when not in use, in order to protect it from dust and contamination.
 - Do not expose to direct sunlight or heat sources.
 - The product must be stored vertically, so that its quality is not compromised.
-

PRINTING METHODS

- Specially developed for solvent, eco-solvent and UV printing.
 - An excessive quantity of ink in the product will result in changes in its characteristics, in inappropriate drying, lamination detachment and / or poor product performance.
 - For the best possible print quality, please make sure you are using the correct print profiles.
 - Inadequate drying can result in curls and wrinkles, which is reflected in the result of the material's performance. A minimum drying period of 48 hours is recommended before any further processing. Drying should be done with the product unrolled.
-

APPLICATION

- Printed materials must be dried properly before processing or application.
 - Do not expose to combustible vapors or spills.
 - Non-vertical application results in a significant reduction in durability, as well as climate and angles of sun exposure.
 - There may be other factors not described here that may influence the performance in the use.
-

IMPORTANT REMARKS

- The user must determine the material's compatibility with the intended specific application, before using it.
- The data provided in this information is based on our knowledge and experience. It is intended to be a source of information and is not a guarantee. It can be subject to change without previous notice.
- We recommend using the same batch of product for a job.
- Decal is not responsible for misuse or improper storage, never being responsible for loss or damage to third parties.

Revision date of the technical data sheet: 23/10/24
Approved by: SC

Please, check our website www.decal-adhesive.com for additional information or request any clarification needed from our technicians.