



260 gr



## Textile BlackBack 260 gr

Polyester blackback fabric with a foamed black back. This fabric is perfect for applications that don't require light penetration, such as curtains, pop-ups, displays, artistic reproductions, etc.

### SUBSTRATE

- Polyester knit

	<i>Value</i>
Finish	Matte
Weight (g/m <sup>2</sup> )	260
Type of Yarn	55Dx50D
Tear resistance (N/5cm)	16.5X18.5
Opacity (%)	75
Clamping temperature °C	190 - 195° C / 30-60 s
Fire behavior (DIN 4102-1)	B1

---

# Textile BlackBack 260 gr

## DURABILITY

- DURABILITY: < 1 year
  - Shelf Life: 24 months from the date of manufacture, applicable only to material that has not been processed, and stored according to the following conditions:
  - This material must be stored at a temperature of  $20^{\circ}\text{C} \pm 5^{\circ}\text{C}$  and  $50\% \pm 5\%$  relative humidity, without major climate deviations.
  - The storage area must be dry and clean.
  - Keep the material in the original package when not in use, in order to protect it from dust and contamination.
  - Do not expose to direct sunlight or heat sources.
  - The product should be stored vertically, so that its quality is not compromised.
- 

## PRINTING METHODS

- Specially developed for direct sublimation and transfer printing.
  - Excessive ink on the product will result in changes to its characteristics, improper drying, delamination, and/or poor product performance.
  - To achieve the best possible print quality, ensure you are using the correct print profiles.
  - Inadequate drying can result in curling and wrinkling, affecting the material's performance.
  - A minimum drying time of 48 hours is recommended before any further processing. Drying should be done with the product unwound.
- 

## APPLICATION

- Printed materials must be adequately dried before processing or application.
  - Do not expose to combustible vapors or spills.
  - Non-vertical application significantly reduces durability, as do climatic conditions and solar exposure angles.
  - Before using the fabric, we recommend it remain at workplace temperature for at least 24 hours.
  - Other factors not described may influence performance during use.
- 

## IMPORTANT REMARKS

- The information provided here is based on our knowledge and practical experience. It is intended as a source of information and does not constitute a guarantee. Subject to change without notice.
- The user must determine the compatibility of the material with the intended specific application before use.
- We recommend using the same batch of material for the same job.
- Decal is not responsible for misuse or improper storage and cannot be held liable for losses or damages to third parties.

Revision date of the technical data sheet: 28/10/24  
Approved by: SC

Please, check our website [www.decal-adhesive.com](http://www.decal-adhesive.com) for additional information or request any clarification needed from our technicians.